



匯統國際股份有限公司
Huey Tung International Co.,

產品規格書 Specification

[Model : HT-4018 / 2012.11.5 version]



Cara Audio Corporation

No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.


Tel: 886-7-310 5786 / Fax: 886-7-310 0783


E-mail: carawang@hueytung.com.tw / <http://www.hueytung.com.tw>

揚聲器製品規格書


SPEAKER SPECIFICATION

型號 Model Number: HT-4018

項目 Items		規格 Specification			
1	公称阻抗 Nominal Impedance	4Ω±5% at 5K Hz 1.0v			
2	最低共振周波数 Lowest Resonance Frequency	2500 Hz±20%Hz Without a baffle			
3	实效周波数带域 Effective Frequency Range	F0~20KHz -10dB			
4	出力音压 Output Sound Pressure Level	90dB±3dB 1W/1M at (12K,14K,16K,18K)Hz AVE.			
5	入力 Input	定格入力 Rated input 10 W	最大入力 Maximum input 20 W		
6	磁束密度 Flux Density	-----±10% GAUSS			
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 6.32 V			
8	动作试验电压 Operation Test	Must be normal at program source 8.94V			
9	极性 Polarity	紅點為正極			
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet:12.5*2 N35 Sub Magnet:	1.80G		
11	连续负荷试验 Life Test	PINK noise 10 W 96 hours			
12	耐热试验 Heat Resistance	70°C±5°C 30%-35%RH 8Hours and then room temperature 1 hours			
13	耐湿试验 Humidity Resistance	40°C±2°C 90%-95%RH 8Hours and then room temperature 1 hours			
14	耐寒试验 Cold Resistance	-25°C±2°C 24 hours and then room temperature 1 hours			
15	落下试验 Drop Test	1M 75°±2°			
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上			
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing			
18	失真率 Distortion	/			
19	各部 材质	Cone Paper	銀亮 PEI		
		Voice Coil	13φ x 8Ω KSV 剝離 180°		
		Cap	/		
20	总重量 Total Weight	/			
		Size: 48mm 試作發行: 2008.8.22	Approve: Arthur	Check: Chen	Design: LIU



成品圖及照片 Mechanical Dimensions : HT-4018



Tolerance: ± 0.5
Unit: mm

