



匯統國際股份有限公司

Huey Tung International Co., Ltd.

產品規格書

Specification

[Model : HT-5062 / 2013.1.17 version]



Cara Audio Corporation


No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.

Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: carawang@hueytung.com.tw / <http://www.hueytung.com.tw>

型號 Model Number: HT-5062 (1200208)

項目 Items		規格 Specification			
1	公称阻抗 Nominal Impedance	4Ω±15% at / Hz 1.0v			
2	最低共振周波数 Lowest Resonance Frequency	2800 Hz±20%Hz Without a baffle			
3	实效周波数带域 Effective Frequency Range	3.5K~20KHz -10dB			
4	出力音压 Output Sound Pressure Level	86dB±4dB 1W/1M at (3K,5K,7K,9K)Hz AVE.			
5	入力 Input	定格入力 Rated input 10 W	最大入力 Maximum input 20 W		
6	磁束密度 Flux Density	-----±10% GAUSS			
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 4.47 V with 3.3UF/100V			
8	动作试验电压 Operation Test	Must be normal at program source			
9	极性 Polarity	/			
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet:12.5*2 N35 Sub Magnet:	/G		
11	连续负荷试验 Life Test	Din45573 noise 10 W 96 hours with 3.3UF 100V	After the Test, Speaker should be meet the Outside and item 7,8		
12	耐热试验 Heat Resistance	100°C±5°C (GB:55°C-70°C) 30%-35%RH 8Hours and then room temperature 1 hours(静态)			
13	耐湿试验 Humidity Resistance	40°C±2°C 90%-95%RH 8Hours and then room temperature 1 hours			
14	耐寒试验 Cold Resistance				
15	落下试验 Drop Test	1M 75°±2°			
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上			
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing			
18	失真率 Distortion	/			
19	各部 材质	Cone Paper	PEI Dome(钛色)		
		Voice Coil	13ΦX4Ω KSV 剥离 30度		
		Plastic material	ABS 777D		
20	总重量 Total Weight	/			
		Size: 40mm 試作發行: 2012.09.06	Approve: Arthur	Check: John	Design: LIU



成品圖及照片 Mechanical Dimensions : HT-5062 (1200208)

