

揚聲器製品規格書

SPEAKER SPECIFICATION

Neodymium Woofer

HT-15ND100



Model : HT-15ND100

specifications		thiele & small parameters		mounting information	
Size	385mm(15in)	Fs	43 Hz	Overall Diameter	393mm(15.5in)
Impedance	8Ω	Re	5.2Ω	Bolt Circle Diameter	374mm(14.7in)
D.C.Resistance	5.2Ω	Qes	0.31	Baffle Cutout Diameter	354mm(13.9in)
Nominal Power	700w	Qms	1.13	Depth	1810mm(7.1in)
Maximum Power	1400w	Qts	0.24	Flange and Gasket Thickness	16mm(0.63in)
Sensitivity(1W/1m)	95.7dB	Vas	100 Ltr	shipping information	
Frequency Range	Fs-1.5KHz	Sd	855cm ²	Net Weight	3.8kg(8.5lb)
Voice Coil Diameter	100mm (4 in)	Xmax	±5.5mm	Shipping Weight	4.6kg(10.2lb)
Winding Material	Aluminium	Mms	146g	Shipping Box	410*410*190mm
Former Material	Glass Fibre	Bl	25.3 T.m		(16.1*16.1*7.4in)
Winding Depth	21mm (0.83 in)	Le	721m mH		
Magnetic Gap Depth	10mm(0.40 in)				
Flux Density	1.25T				
Magnet Material	NNeodymium Inside Slug				

Also available in 4Ω and 16Ω , data upon request

SPL vs Freq



Impedance vs Freq

